

SEEPLEX100

Specifications:

Internal: Non-toxic, non-radioactive low profile exit solution.

Visible at up to 100 feet.

External:

Construction: ABS plastic with photoluminescent panel. Can be used for high and/or low level installations and has a 25 year life expectancy. It is visible at 100 feet during a blackout condition. Meets current building codes, NFPA Life Safety Code 101 and OSHA requirements; International Building Code 2009/2018; International Fire Code 2009/2018.

Electrical

CIRCUIT: Since there is no electricity required, this fixture is a safer signage solution, which saves on maintenance and energy costs.

INSTALLATION: Before installation it must be determined that there is a minimum of 5 Fc of LED, Fluorescent, metal halide or mercury vapor light on the face(s) of the sign at all times during building occupancy.

MECHANICAL: Utilizes photoluminescent technology which absorbs and stores ambient light. It is a non-toxic, and non-radioactive low profile emergency lighting solution. Featuring field adjustable chevrons and is constructed of ABS plastic with photoluminescent panel. NON-TOXIC and NON-RADIOACTIVE which eliminates disposal fees.

WARRANTY: 10 year factory warranty. Deliberate damage, misuse, improper installation effectively cancel the warranty.



EXAMPLE:SEEPLEX100-P1-WG-UB

Series	# of Faces	Frame Color	Mounting
SEEPLEX100	P1 (single)	R (red- no lettering outline)	UB (universal mounting bracket)
	P2 (double)	G (green- no lettering outline)	
		B (black- no lettering outline)	