

JOB NAME: _____

TYPE: _____ PART #:

NOTES:

SEELEDXR LED High Output Industrial Emergency Unit

ILLUMINATION:

• Ultra-bright, energy efficient, long-life White LED adjustable lamp heads provide up to 100-ft center-to-center spacing with a 6-ft path of egress at 15-ft mounting height.

- 6.0 watt (12 LEDs x 0.50 watt) per head.
- Adjustable glare-free PAR-Type lamp heads with all-inclusive lamp, reflector and lens assembly.

ELECTRICAL:

• Dual 120/277 voltage.

• Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.

- LVD (low voltage disconnect) prevents battery from deep discharge.
- 6V/12V maintenance-free, rechargeable sealed lead acid battery.
- output) standard on the 50W, and 100W models.
- Offers 38.0W and 88.0W or Remote Capacity (6V/12V DC

• Internal solid-state transfer switch automatically connects the internal

battery to lamp heads for minimum 90-minute emergency illumination.
Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING:

- Knockouts on the back for wall mount.
- · Side and top knockouts for conduit feed applications.

HOUSING:

• Injection-molded, engineering grade, 5VA fl ame retardant, highimpact thermoplastic construction.

WARRANTY / LISTING:

• Five year warranty on all electronics and housing. Battery pro rated for two years.

Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.

UL Listed for damp locations (20°C – 40°C).



REMOTE LAMP COMPATIBILITY

MODEL NUMBER	BATTERY	REMOTE	COMAPATIBLE REMOTE HEAD FAMILY				
		CAPACITY	HPRL	RHLED-MV	RH16LED	SRHLED	
SEELEDXR65	6V	38W	Х	Х	Х	Х	
SEELEDXR610	6V	38W	Х	Х	Х	Х	
SEELEDXR125	12V	88W	Х	Х	Х		
SEELEDXR1210	12V	88W	Х	Х	Х		

ORDERING INFORMATION


Sample Part Number: SEELEDXR	MODEL	VOL	TAGE	0	CAPACITY	HOUSIN	G COLOR
Sample Fait Number. SELLEDAN	SEELEDXR	6 12	6 Volts 12 Volts	5 10	50 Watt 100 Watt	(blank) B	White Black



DIMENSIONS

50 Watt





ELECTRICAL INFORMATION

CATALOG NUMBER	INPUT W	ATTS (W)	INPUT AMPS (A)		
	120V	277V	120V	277V	
SEELEDXR65	16.0	16.0	0.15	0.06	
SEELEDXR610	30.0	30.0	0.28	0.12	
SEELEDXR125	16.0	16.0	0.15	0.06	
SEELEDXR1210	30.0	30.0	0.28	0.12	